

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



(43) International Publication Date
23 December 2004 (23.12.2004)

PCT

(10) International Publication Number
WO 2004/111591 A1

(51) International Patent Classification⁷: G01L 3/14, (74) Agent: GRIEBLING, Onno; c/o Octroobureau Griebling B.V., Sportweg 10, NL-5037 AC Tilburg (NL).

(21) International Application Number:
PCT/NL2004/000425

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(22) International Filing Date: 14 June 2004 (14.06.2004)

(25) Filing Language: Dutch

(26) Publication Language: English

(30) Priority Data:
1023681 17 June 2003 (17.06.2003) NL
1023765 27 June 2003 (27.06.2003) NL

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).


(71) Applicant (for all designated States except US): SPIN-POWER B.V. [NL/NL]; Muldersweg 8, NL-5051 NN Goirle (NL).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: TRANSMISSION SYSTEM, AND METHOD FOR MEASURING A DRIVE FORCE THEREIN



(57) Abstract: A transmission system (1), for instance of a bicycle, is described, comprising a drive wheel (2), a driven wheel (3), and a coupling chain (4) having a first chain half (4C) and a second chain half (4D). The transmission system is provided with a measuring device (6) for providing a measurement signal which is representative for the torque transmitted by the coupling chain (4). This measuring device (6) comprises a transverse force sensor arranged within the span of the coupling chain (4) in the form of a wheel (10) rotatably mounted on a supporting arm (20), which wheel touches the first chain half (4C) and the second chain half (4D). The measuring device provides a measurement signal which is a measure for the component (Fv), directed substantially perpendicular to the plane (L) defined by the rotation axes of the drive wheel (2) and the driven wheel (3), of the resultant (FDR) of the transverse forces (FDC, FDD) exerted to the sensing wheel (10) by the chain halves (4C, 4D).

WO 2004/111591 A1